

ASK Proxima M5 and Ultralight DX3 Projectors

Technical and Functional Specifications

Native Resolution	<ul style="list-style-type: none">• XGA (1024 x 768)
Resolution Supported	<ul style="list-style-type: none">• VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), SXGA (1280 x 1024)
Brightness	<ul style="list-style-type: none">• 1100 ANSI lumens
Brightness Uniformity	<ul style="list-style-type: none">• 80%
Contrast Ratio	<ul style="list-style-type: none">• 600:1
Computer Compatibility	<ul style="list-style-type: none">• IBM PC or compatibles• Apple Macintosh
Video Compatibility	<ul style="list-style-type: none">• PAL, PAL-M, PAL-N, SECAM, NTSC 3.58, NTSC 4.43
Display Technology	<ul style="list-style-type: none">• Single-chip DLP
Number of Colors	<ul style="list-style-type: none">• 16.7 million color
Input Sources	<ul style="list-style-type: none">• 1 digital computer (DVI), 1 analog computer, 1 S-video, 1 composite video, 1 audio, 1 USB mouse
H-Sync Range	<ul style="list-style-type: none">• 15 - 100 kHz
V-Synch Range	<ul style="list-style-type: none">• 43.5 - 130 Hz
Bandwidth	<ul style="list-style-type: none">• 160 MHz analog• 112 MHz digital
Keystone Correction (digital)	<ul style="list-style-type: none">• $\pm 11^{\circ}$ - 13.5° adjustable, 110% offset
Projection Lens	<ul style="list-style-type: none">• focal length 30 mm to 37.5 mm F/2.6
Projection Distance	<ul style="list-style-type: none">• 1.1 m to 10 m (3.6'-32.8')
Zoom	<ul style="list-style-type: none">• 1.25:1 manual zoom
Aspect Ratio	<ul style="list-style-type: none">• 4:3
Image Size (diagonal)	<ul style="list-style-type: none">• 2.1 ft. to 23.4 ft. (.6 m to 7.1 m)
Throw Ratio	<ul style="list-style-type: none">• 1.72 - 2.15:1
Audio	<ul style="list-style-type: none">• 2 x 1 watt stereo
Remote Control	<ul style="list-style-type: none">• Full function remote with laser pointer and mouse control
Lamp (Life)	<ul style="list-style-type: none">• 120-watt UHP (2,000 hours)
Dimensions	<ul style="list-style-type: none">• 9.6 in. W x 7.7 in. L x 2.7 in. H• 24.5 cm W x 19.5 cm L x 6.8 cm H
Weight	<ul style="list-style-type: none">• 5 lbs. (2.3 kg)
Power Consumption	<ul style="list-style-type: none">• < 180 watts
Power Requirements	<ul style="list-style-type: none">• 90V - 264V AC, 47/63 Hz
Operating Temperature	<ul style="list-style-type: none">• 59° to 95° F (15° to 35° C)
On-Screen Languages	<ul style="list-style-type: none">• English, French, Spanish, Portuguese, German, Italian, Chinese, Korean, Japanese, Norwegian
Audible Noise	<ul style="list-style-type: none">• < 35 dB
Approvals	<ul style="list-style-type: none">• CE, UL, cUL, FCC Class A
Warranty	<ul style="list-style-type: none">• two years on parts and labor• 90 days limited on lamp• two years of ProXchange replacement service